

# Product Data Sheet

## Floor Polish



Product	Floor Polish - Clear or Dark
Description	A soft, penetrating beeswax-based polish, designed to nourish dry timber floors. Buffs to a soft, natural sheen.
Size	200ml, 1L, 2L
Used For	Raw timber floorboards.
Surface Preparation	Ensure the timber is well sanded and smooth. We recommend using a sanding sealer to reduce the amount of wax needed. Apply before waxing.
How to Apply	<ol style="list-style-type: none"> <li>1. Dip a soft, lint-free cloth into the tin and scrape out a small amount. Rub into the timber with pressure in line with the grain.</li> <li>2. Buff back any excess with a soft, lint-free cloth or buffing pads.</li> <li>3. Use up to three coats particularly if the timber is very porous, buffing well between coats. Allow up to an hour between coats to allow waxes to sink right in.</li> </ol> <p>If using an electric polisher, spread a small amount of wax directly onto the brushes and spread it over the floor with the polisher. Buff back using buffing pads or soft brush fittings.</p>
Dry Time	Minimum 30 minutes. Ensure the surface is touch dry with no fingerprinting before applying the next coat.
Maintenance	Depending on wear, as the surface becomes dull or dry.
Clean Up	Warm, soapy water for hands or cloth. Excess wax on timber; dampen a cloth with d-Limonene or mineral turpentine.
Safety	<ul style="list-style-type: none"> <li>• Keep out of reach of children</li> <li>• Contains mineral solvent</li> <li>• Hang out rags to dry, or soak in water. Don't leave scrunched up</li> <li>• May contain traces of bee pollen &amp; soy</li> <li>• Contact Gilly's for SDS</li> </ul>
Ingredients	Beeswax, microcrystalline wax, carnauba wax, plant oil, low-odour mineral solvent

Image



**W:** [www.gillyswaxesandpolishes.com.au](http://www.gillyswaxesandpolishes.com.au)  
**E:** [info@gillyswaxesandpolishes.com.au](mailto:info@gillyswaxesandpolishes.com.au)  
**T:** (08) 9295 1973