


Product Data Sheet

Kitchen Bench Oil



Product	Kitchen Bench Oil: For Timber Benchtops
Size	250ml
Description	<p>A tung oil based finish designed for timber bench tops, tables and other surfaces in need of a hard wearing natural finish.</p> <p>Kitchen Bench Oil contains natural oils such as tung oil, which helps to seal timber and protect it from general wear. Importantly, it will also repel water. This makes it a great product for kitchen benches, laundry benches and bathroom benches that contain timber tops that may get exposed to water.</p> <p>This oil contains no lacquer or silicon, unlike many products on the market, which means easier maintenance for you and a beautiful natural finish. It will highlight the nuances of your selected timber and prolong its natural look.</p>
Used For	Kitchen benches, bathroom & laundry benches, cabinetry, butcher blocks, dining tables, window frames
Surface Preparation	<p>Ensure the surface is clean and dry before application. D-limonene (natural citrus solvent) or a turpentine can be used for a vigorous clean. For a lighter clean, you can use an all purpose cleaner.</p> <p>If there is any oil, wax, grease, dirt or similar residue on the surface, it may affect the tung oil's ability to cure - so a thorough clean is important.</p>
How to Apply	<ol style="list-style-type: none"> 1. Rub or brush oil into the timber. Lighter coats are better. 2. Let it sit for 5 minutes. Wipe on more oil to areas that become dull, as the oil soaks in. 3. Wipe off the excess oil, then lightly sand back whilst still damp. Use 320 grit or finer. 4. Apply 3 coats, repeating the same procedure. Best to wait 24 hours between coats. Apply more coats if desired or necessary. 5. Hang out any rags or soak in water.
Dry Time	24 hours to dry between coats. As this is tung oil based, it can take 4 weeks to completely cure. Light usage is however perfectly fine within this time.

<p>Maintenance</p>	<p>This product is built from natural oils, in particular tung oil. This makes for a beautiful natural finish. If you do find the finish gets scratched or damaged, you can simply reapply following the same steps outlined above. There is no need to sand it back as you would with lacquers, varnishes and silicon based products.</p> <p>For general maintenance and wear, you can assess as you see fit. We would recommend reapplying a light 1-2 coats every 6-12 months to keep your timber looking fresh.</p>
<p>Clean Up</p>	<p>D-Limonene or mineral turpentine.</p>
<p>Safety</p>	<ul style="list-style-type: none"> ● Use in a well ventilated area. Wear a protective mask, if in enclosed space. ● Gloves are recommended ● Hang out rags to dry, or soak in water. Don't leave scrunched up. ● May contain traces of bee pollen & soy ● Contact Gilly's for SDS
<p>Ingredients</p>	<p>Tung oil, plant oils, litsea cubeba essential oil, citrus terpene, soy bio-solvent, low odour solvent</p>
<p>Image</p>	

W: www.gillysaustralia.com.au
E: orders@gillysaustralia.com.au
Ph: (08) 9295 1973